PJD6211P

Versatile, Portable XGA DLP Projector

120HZ, 3D-READY

Price/performance leader in portable DLP projectors.

ViewSonic's PJD6211P DLP®projector is ideal for use in the office or on the road. It delivers amazingly clear images with the digital clarity of DLP's BrilliantColor™ technology. This budget-friendly projector boasts amazingly fast 120Hz frame rate and is 3D ready for commercial 3D applications and 3D games at home. With high contrast ratio, brightness and ViewMatch™ technology to adjust colors perfectly, your presentations will be rich, vibrant regardless of the setting. Multiple preset presentation modes, an increased ±40 degree digital keystone correction and powerful 1.1x optical zoom ensure the best possible image regardless of location. With up to 5000 hours of lamp life, low cost replacement lamps, filter-less design and a non-degrading DLP light engine, the PJD6211P has one of the best "TOTAL COST OF PROJECTION" ratios in the industry.

OUTSTANDING PRESENTATIONS

> **Bright in virtually any setting**
Packs 2500 ANSI lumens in just 2.6kgs, and with a high 2000:1 contrast ratio (typ), your presentations are guaranteed to be vibrant even in the brightest office environment.

> **BrilliantColorTM technology**
Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 6-segment colour wheel enriches the yellow colour performance that is key to accurate and vivid colour reproduction.

> **Low total cost of ownership**
Make the most of your projector investment with long life lamps with up to 5000 hours lamp life and a filter-less dust resistant design that reduces maintenance costs.

> **Protect your investment**
Assign a PIN code to password protect the projector from unauthorized use or theft.

> **The perfect setup convenience**
The automatic vertical keystone correction (+/- 40 degrees), aspect ratio adjustment and powerful 1.1x optical zoom ensures a perfect image in any room. Adjustable feet let you adjust the image at even higher viewing angles.

> **Industry leading warranty**
Enjoy full peace of mind with a generous 3 years on-site product warranty and a limited one year lamp warranty.

MORE THAN 2000 AWARDS

VIEWSONIC
PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic®
See the difference™

PJD6211P

ViewSonic® See the difference™

Versatile, Portable XGA DLP Projector

Model No.VS12618

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024×768 (Native) / SXGA 1280×1024 (compressed)
	Lens	1.1× Manual optical zoom/ Manual optical focus
	Keystone	Vertical digital keystone correction: ± 40 degrees
	Size	27"-300"
	Throw Distance	1.2m-10m
	Throw Ratio	1.97-2.17
	Lamp	180watt (RLC-050)
	Lamp Life	4000 / 5000 hrs
	Brightness	2,500 Lumens
	Contrast Ratio	2000:1 (with DCR)
	Aspect Ratio	4:3 & 16:9
	Color Depth	24 bits, 16.7M Colors (8+8+8)
	Color Wheel	6-Seg RGBCYW / 7200rpm
	Color Gamut	85 % NTSC 1931 CIE
AUDIO	Speaker	2W x 1
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25pfs and 30fps)
	Frequency	Fh: 31-100 KHz, Fv: 50-120 Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac	Up to 1024×768 (may require Mac Adapter)
CONNECTOR	RGB Input	2 × 15-pin mini D-sub
	RGB Output	1 × 15-pin mini D-sub
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	1 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1 × RS-232 (9 Pin D-sub)
	USB	1 x type B
POWER	Voltage	90~240VAC(Auto Switching), 50/60Hz (universal)
	Consumption	235W (Typical) / <1W (Stand-by mode)
LANGUAGE		English / Dutch / French / Spanish / Italian / Korean / Thai / Portuguese / T. Chines / S. Chinese / Japanese / Russian / German / Swedish / Turkish / Finnish / Polish
CONTROLS	Basic	POWER, Keystone/Arrow keys, Left/BLANK, MENU/EXIT, Right/Panel key lock, AUTO, MODE/ENTER, SOURCE
	OSD	Picture: Brightness, Contrast, Color Setting, Keystone, Aspect Ratio, Image, White Intensity, Gamma, 3D Sync, 3D Sync Invert. Computer Image: Frequency, Tracking, H Position, V Position Video Image: Saturation, Sharpnes, Tint Setting: Manu Position, Projection, Signal Type, Lamp Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter Hours Reset,Power Saving, Auto Source, ECO Mode, High Altitude, OSD Timeout Advance:Blank Screen, Password Word, Screen Capture, Start up Screen, Text Shot: Digital Zoom, DCR, Close Captions, Brilliant Color
OPERATING CONDITION	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10%-90% (non-condensing)
	Altitude	0~6,000 ft (1,800 m), operational up to 10,000 ft (3048 m) at reduced reliability and performance
NOISE LEVEL	Normal/ Eco Mode	31dB/ 29dB
DIMENSIONS (W x D x H)	Physical	280 x 114 x 218 (mm) / 11 x 4.25 x 8.58 (in)
WEIGHT	Net	2.6 kg (5.7 lb)
REGULATIONS		CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOMPSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC
WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp

Optional Accessories

Replacement lamp RLC-050
Wireless presentation gateway WPG-360
DLP Link 3D Glasses.....PGD-150
Universal soft case PJ-CASE-001

Projection Distance		4:3 Screen Screen Size			
		Wide		Tele	
M	feet	m	inch	m	inch
1.5	4.92	0.99	38.85	0.89	35
1.8	5.90	1.18	46.62	1.07	42
2	6.56	1.32	51.80	1.19	47
3	9.84	1.97	77.70	1.79	70
5	16.40	3.29	129.51	2.98	117
10	32.80	6.58	259.01	5.95	234

RoHS COMPLIANT

ISO 9001:2000 FM 40187
ISO 14001:1996 FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Rev.1.0

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required.

Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies.

VSE 2010/08/26 V3

For more product information, visit us on the web at viewsoniceurope.com